



LASER RANGE FINDERS

CLOSE RANGE LASER RANGEFINDER MONOCULARS LRM 1200 / LRM 1500 / LRM 1500SPD

Close range Laser Rangefinder Monocular series comprises three models suitable for wide variety of tasks from amateur hunting to sniper and artillery shooting. All devices in the line are manufactured in unified ergonomic lightweight case with rubberized grip. These advanced Laser Range Finder systems provide instant distance and speed (SPD modification) measurements consistently and accurately. The outstanding optics allows a sharp, clear image under all conditions. LRM models utilize a revolutionary digital design, which outperforms any other product in its class and price range.



- 1 - Measurement result
- 2 - Units of measurement (Yards, Meters, KMH, MPH, Mills, degrees)
- 3 - Low battery indicator
- 4 - Over 100m indicator (optional)
- 5 - Laser active indicator
- 6 - Target quality indicator (optional)
- 7 - Reticle (cross or rectangular selectable)

MANUFACTURER	NEWCON-OPTIK			BUSHNELL*	BUSHNELL* NIKON*
	LRM 1200	LRM 1500	LRM 1500 SPD	BUSHNELL 1000	BUSHNELL 800 NIKON 800
MODEL					
1. Optics	Class 1 eye safe				
Magnification, x		7		6	8
Objective lens, mm		25		21	27
Field of view, °		8°		5.7°	4.6°
2. Range Finder					
Measuring range, m	20-1,200	20-1,500	20-1,500	25-1,300	20-800
- Max. distance, m (white target)	1140	1460	1460	968	800
- Max. distance, m (black target)	436	608	608	406	302
Accuracy, m	± 1	± 1	± 1	± 1	± 2
Meters/Yards display	√	√	√	√	√
Target quality indicator	√	√	√	√	√
Last 10 readings recall	√	√	√	-	-
Reticle shape selection (+ or □)	√	√	√	-	-
Scan mode	√	√	√	-	√
Automatic rain mode	√	√	√	-	-
Automatic >100m mode	√	√	√	-	-
Reflective mode	√	√	√	-	-
'Last Target' measurement	√	√	√	-	-
Optional speed detector	-	-	√	-	-
3. Miscellaneous					
Battery		9 V		9 V	AAA(4)
Low battery indicator		√		√	√
Tripod socket		√		√	-
Weight without battery, g		420		385	326
Dimensions, mm		120x122x60		121x127x57	95x121x51
Country of origin		Canada		Japan	China



* DATA FOR COMPARISON ONLY. PRODUCT IS NOT FOR SALE.
 THE ABOVE TABLE IS CONFIDENTIAL AND CANNOT BE USED WITHOUT NEWCON'S WRITTEN PERMISSION.